

## The Ideal Communication System for installations where a security gate or shade is used

For those times when it's impractical, for various reasons, to mount the inside control section of a communicator on a window with a secure gate the Norcon TTU-7X is the communication system of choice. The prism shaped control unit of the TTU-7X is ideal for mounting on a counter top on the interior side of a barrier. The system allows hands free communications through barriers typically found in banks, cashier's booths, information booths and similar environments.

The TTU-7X incorporates the same high-quality electronics as the basic Patent Pending (#4049911) Norcon TTU-1 Talk-Thru system. It is a vox system, enabling the attendant and the customer to have hands free two way communication.

The TTU-7X provides clear communication even in environments with high ambient noise by shaping the sound for maximum intelligibility. Its compression circuitry decreases loud, annoying sounds.

The TTU-7X Talk-Thru Communicator now incorporates circuitry to automatically attenuate the outside channel. If the gooseneck microphone is not used for a period of 30 seconds, the outside channel volume will be reduced

approximately 70%. Normal operation is restored as soon as the attendant speaks into the gooseneck microphone. The automatic volume attenuation circuit prevents outside noise from bothering the attendant.

The TTU-7X is equipped with a jack to add a headset or wireless microphone. Simply plug the headset in and communicate. The headset features include light weight construction, a boom mic and a single speaker that covers one ear.

### HOW TO INSTALL...

Installation of the TTU-7X is a very simple, one-person operation. All that's needed is a 3 - 4 inch cutout in the barrier. All hardware and cable are supplied.

**Please specify barrier thickness when ordering.** The prism unit is quickly and easily mounted on the counter-top on the inside of the barrier, at a convenient location for the user. A power adapter and all cables are supplied. The TTU-7X comes with a continuous-duty, 90-240 VAC 1 Amp power supply which is stepped down to 15 Volts.



Inside Unit (Attendants Side)



# Norcon TTU-7X Talk Thru System™

## FEATURES

- Clear 2-way hands-free voice communication (vox).
- Quality electronic design and engineering.
- Avoids shouting, repetition, misunderstanding.
- Rugged, tamper-resistant materials.
- Removable 18" XLR mic. Optional 8" and 24" mic available on request
- Simple, one-person installation. Compact, contemporary design. Fits any decor.
- Export models available.
- Bullet resistant option.
- Units available for ADA applications.
- Built in U.S.A with local and imported components
- Built in jack for headset

## SPECIFICATIONS

### MECHANICAL

- Outside assembly:  
5 in. dia x 1/2 in. deep outside; 1 in. deep inside; solid aluminum, clear anodized finish, tamper resistant.
- Inside assembly:  
6 in. W x 2<sup>3</sup>/<sub>8</sub> in. H x 2<sup>3</sup>/<sub>8</sub> in. D Machined aluminum, clear anodized finish, tamper resistant. weight: 2 lbs.
- Mounting: window / countertop

Inside assembly Panel

Controls: Listen volume, Talk volume, power on/off, LED

## ELECTRONIC

- Audio frequency response: Selectively shaped for maximum voice intelligibility
- Audio power: 2 Watts per amplifier (2 amplifiers)
- Distortion: Less than 2%
- Listen mode: 20 dB compression
- Talk mode: Vox
- Microphones: Electret
- Power supply:  
Input: 90-240 VAC, 60 Hz  
Output: 15 VDC, 1A  
CE,UL approved Level VI power adapter

Talk-Thru systems are shipped complete with cables, 22" of matching anodized aluminum tubing to conceal wiring instructions, and power supplies. Mounting hardware is not included.

Specifications are subject to change without notice.

## Other available models

- ◆ TTU-1AX Continuous power unit complete  
Housing depth is 2 1/2 in.
- ◆ TTU-1ABX same as TTU-1A, but with bullet-resistant option (UL Level 3)
- ◆ TTU-1DX Battery operated unit complete with rechargeable batteries and charger. Housing depth is 3 1/2 in.
- ◆ TTU-1DBX same as TTU-1DX, but with bullet-resistant option (UL Level 3)
- ◆ TTU-NC noise cancelling Talk-Thru unit now incorporates circuitry to automatically attenuate the outside ambient noise by 26db to 30db. This feature can be added, on to any of the Talk thru communicators models, except the battery operated TTU-1DX. Ideal for high ambient noise environment
- ◆ TTU-NCHS wired Headset for TTU products
- ◆ TTU-WHS Wireless headset for TTU products